



No.235DOC-0112

Doc No.	D2B006
	D3B034
	D5B064

EU Declaration of Conformity

Identification of the Product	φ 22 Emergency Stop Switches
Name and address of Manufacturer IDEC CORPORATION 2-6-64 Nishimiyahara, Yodogawa-Ku, Osaka 532-0004 Japan	Name and address of the authorized representative : APEM SAS 55, Avenue Edouard Herriot BP1, 82303 Caussade Cedex, France

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration : Series Name – HW Series

Model No. – Details are as per attached sheet

The object of the declaration described above is in conformity with the relevant EU harmonization legislation :

2014/35/EU

Low Voltage Directive

2006/42/EC

Machinery Directive

2011/65/EU and (EU)2015/863

Restriction of the use of certain hazardous substances
(RoHS) Directive

Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.

EN 60947-5-5/A2:2017

EN IEC 63000: 2018

Where applicable, the notified body

Additional Information :

Signed for and on behalf of the above named manufacturer :

Place and date of issue :

Japan, 20 April, 2016

Name, function :

Japan, 18 November, 2021 (Revised)

Masaki Tsuru, Executive Officer

Quality Assurance Center

Signature :

Doc No.	D2B006
	D3B034
	D5B064

20 April, 2016
 20 July, 2020 (Revised)
 Page 1 of 2

Pushlock Turn Reset or Pushlock Key Reset Switch

HW 1 B - V 3 F 01 N1 4 - MAU - *****
I II III IV V VI VII VIII IX X XI

- I: Series HW
- II: Bezel shape
 - 1 ----- Round
 - 4 ----- Round, metal type
- III: Operator function
 - B ----- Non-illuminated pushbutton
- IV: Function
 - V ----- Pushlock turn reset
 - X ----- Pushlock key reset
- V: Operator shape
 - 3 ----- Mushroom
 - 4 ----- Jumbo mushroom
 - 5 ----- Extra-Jumbo mushroom
- VI: Applicable contact block
 - None ----- With HW-G or HW-U series contact block
 - F ----- With HW-F or HW-U series contact block
 - C ----- With HW-C series contact block
 - P ----- With HW-P series contact block
- VII: Contact configuration
 - Two alphanumeric characters – to specify NC/NO contact(s)
- VIII: Contact blocks mounting position
 - None, N1, N2, N3, N4, N5, N6, N7, N8 or N9
- IX: Button color
 - R/R ----- Red
 - R-EMO/R-EMO----- Red, EMO by SEMI Standard
 - R-EMO-2/R-EMO-2-----Red, EMO by SEMI Standard
- X: Special Contact
 - MAU ----- Gold plated contact
 - None ----- Normal contact
- XI: Manufacturer Control No. (may be followed)
 - Any suffixes, nine digits max.

Doc No.	D2B006
	D3B034
	D5B064

20 April, 2016
 20 July, 2020 (Revised)
 Page 2 of 2

Push-Pull Switch

HW 1 B - Y 2 F 01 N1 R - MAU - *****
I II III IV V VI VII VIII IX X XI

- I: Series HW
- II: Bezel shape
 - 1 ----- Round
 - 4 ----- Round, metal type
- III: Operator function
 - B ----- Non-illuminated pushbutton
- IV: Function
 - Y ----- Push-pull
- V: Operator shape
 - 2 ----- 2 positions maintained
- VI: Applicable contact block
 - None ----- With HW-G or HW-U series contact block
 - F ----- With HW-F or HW-U series contact block
 - C ----- With HW-C series contact block
 - P ----- With HW-P series contact block
- VII: Contact configuration
 - Two alphanumeric characters – to specify NC/NO contact(s)
- VIII: Contact blocks mounting position
 - None, N1, N2, N3, N4, N5, N6, N7, N8 or N9
- IX: Button color
 - R/R -----Red
- X: Special Contact
 - MAU -----Gold plated contact
 - None -----Normal contact
- XI: Manufacturer Control No. (may be followed)
 - Any suffixes, nine digits max.